

FLOREY[®] Polyether defoamer

Defoamer for concrete or mortar

Product Description

This product is a defoamer for concrete and mortar in accordance with GB8076 concrete admixtures. Polyether defoamer is one of the most important varieties of defoamer products, with non-toxic, odorless, non-irritating and easily dispersed in water characteristics, in addition to general industrial applications, but also can be used in concrete, mortar, food, fermentation, cosmetics and pharmaceutical industries.

Applications

- Water-reducing agent, waterproof and oil-repellent agent, detergent added.
- Fermentation, power plant, circuit board cleaning and other industries defoaming;.
- Oilfield industry.
- ■The decomposition tank and the red mud washing tank in the aluminum oxide plant can eliminate bubbles.

Product characteristics

- It is composed of polyether ester, dispersant and stabilizer.
- Anti-bubble effect is outstanding.
- Easy to disperse in water.

Product specification

Main component: Polyether ester, dispersant and stabilize

Appearance: Milky liquid
Odour: Odorless
Density(g/cm3): 1.08±0.05

Guidelines for Use

- 1. The defoamer has excellent anti-foam and anti-foam performance. It can be added after the foam is generated or added into the product as a anti-foam component. According to different use systems, the addition amount of the defoamer can be $10\sim1000$ ppm, and the best addition amount is determined by the customer according to the specific situation.
- 2. Defoamer products can be used directly or diluted. If it can be fully stirred and dispersed in the foaming system, it can be directly added without dilution.
- 3. Do not add acid, alkali, salt and other substances to this product. Seal the container when not in use. If there are layers for a long time, stir evenly, generally does not affect the use of the effect.

Storage and Handling

Storage Temperature: Products should be stored in $0^{\circ}\text{C}-30^{\circ}\text{C}$ temperature environment, without direct sunshine, without getting wet in the rain and leaking water, without mixing impurities, without evaporation of water.

Shelf Life: It has a minimum shelf life of 6 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your us regarding suitability for use and dosage recommendations if the shelf life has been exceeded.

Packaging

This product is packaged in 25kg, 50kg or 200kg plastic drums.

Henan Fuluorui New Materials Co., Ltd. Luoyang Florey Import and Export Co.,Ltd

https://floreyconcrete.com

ROOM O1, BUILDING 8, JUNHE YUNGU, SOUTHEAST CORNER OF THE INTERSECTION OF GUANGWU AVENUE AND LANTAI ROAD, YIBIN DISTRICT, LUOYANG CITY, HENAN PROVINCE 471000 Tel: +86 0379-68883868 Fax: +86 0379-68883868

TEL: +86 13783184240 E-mail: lucylu@floreyconcrete.com